


SCALA V2 UTOPIA™

Specification sheet



The three-way floor standing loudspeaker Scala V2 has retained all the qualities of the previous version which has been unanimously acclaimed by the most discerning audiophiles world wide for over 5 years: a beautiful design, unbelievable musicality and easy to install. The Scala V2 now boasts a new bass unit providing improved power handling, giving more effective bass and enhanced control. This has also improved the midrange register whose focus has progressed immensely, resulting in a more precise and remarkable sound stage. The Scala V2 takes you closer to the music with enhanced emotion and listening pleasure.

- 1 **6 1/2" (16.5cm) Power Flower midrange "W" driver**
 - > 3rd generation W composite sandwich technology, laser cut-out
 - > Power Flower magnet, maximal power and reduced magnetic leaks
- 2 **IAL2 pure Beryllium inverted dome tweeter**
 - > very large bandwidth from 1 to 40kHz
 - > IAL2 (Infinite Acoustic Loading): low resonance frequency at 580Hz
 - > definition, rapidity and transparency of the midrange/treble
- 3 **11" (27cm) "W" woofer**
 - > 3rd generation W composite sandwich technology, laser cut-out
 - > high power handling - more impact
- 4 **High section laminar port**
 - > no air flow or distortion noises
 - > no dynamic compression of the bass
- 5 **Focus Time**
 - > mechanical phase optimization of the drivers
 - > driver orientation towards the listener
- 6 **Gamma Structure**
 - > MDF panels up to 2" (5cm) for a stable mechanical reference
 - > anti-vibration heavy structure, optimized by vibratory cartography
- 7 **OPC+ filtering**
 - > Bass adjustment on ± 1 dB, treble on ± 1.5 dB
 - > audiophile type components
 - > WBT connectors



Removable tweeter and woofer grilles

Key points

- A 3-way reference floorstanding loudspeaker
- Very high-end but with moderate size
- Utopia III technologies: Beryllium, IAL2™, Focus Time™, OPC+™, W™, Power Flower™, Gamma Structure™
- Sound personalization with adjustable bass and treble levels
- 100% Focal manufactured



Type	3-way, floorstanding bass-reflex loudspeaker
Drivers	11" (27cm) "W" woofer Power Flower 6 1/2" (16.5cm) "W" Midrange IAL2 pure Beryllium inverted dome 1" (27mm) tweeter
Frequency response (+/- 3dB)	27Hz - 40kHz
Response at - 6dB	24Hz
Sensitivity (2.83V / 1m)	92dB
Nominal impedance	8 Ω
Minimal impedance	3.1 Ω
Filtering frequencies	250Hz / 2200Hz
Recommended amp power	40 - 500W
Dimensions (H x L x D)	49 1/8 x 15 1/2 x 26 3/8" (1247 x 393 x 670mm)
Weight	187.4lb (85kg)